

Spectrum Media and Wrapper Formats

Release: 8.3

Date: 31 July 2017

Rev. A

Notice:

Copyright 2017 Harmonic Inc. All rights reserved.

Harmonic, the Harmonic logo, [all other Harmonic products mentioned] are trademarks, registered trademarks or service marks of Harmonic Inc. in the United States and other countries. All other trademarks are the property of their respective owners. All product and application features and specifications are subject to change at Harmonic's sole discretion at any time and without notice.

Disclaimer:

Harmonic reserves the right to alter the product specifications and descriptions in this publication without prior notice. No part of this publication shall be deemed to be part of any contract or warranty unless specifically incorporated by reference into such contract or warranty. The information contained herein is merely descriptive in nature, and does not constitute a binding offer for sale of the product described herein. Harmonic assumes no responsibility or liability arising from the use of the products described herein, except as expressly agreed to in writing by Harmonic. The use and purchase of this product does not convey a license under any patent rights, copyrights, trademark rights, or any intellectual property rights of Harmonic. Nothing hereunder constitutes a representation or warranty that using any product in the manner described herein will not infringe any patents of third parties.

Third-Party Product Trademarks:

Adobe® After Effects®, Photoshop®, Flash® Professional, Premiere® Avid® Media Composer® Jünger Audio™ Apple® QuickTime® Microsoft® Mediaroom® Microsoft® PlayReady® DOCSIS® 3.0 Start Over® TV Dolby is a registered trademark of Dolby Laboratories. Dolby Digital, Dolby Digital Plus, Dolby Plus, aacPlus, AC-3, and Dolby® E are trademarks of Dolby Laboratories. Level Magic and Jünger are trademarks of Jünger Audio Studioteknik GmbH. MPEG Audio technology licensed from Fraunhofer IIS <http://www.iis.fraunhofer.de/amm/> PitchBlue® is a registered trademark of Vigor Systems. QuickTime and the QuickTime logo are trademarks or registered trademarks of Apple Computer, Inc., used under license therefrom.

Third-Party Copyright Notes:

Harmonic software uses version 3.15.4 of the FreeImage open source image library under FreeImage Public License (FIPL). See <http://freeimage.sourceforge.net> for details. The product may include implementations of AAC and HE-AAC by Fraunhofer IIS; and MPEG Audio technology licensed from Fraunhofer IIS. The software described in this publication may use version 2.8 of FFmpeg open source package under Lesser General Public License (LGPL).

Table of Contents

Media Formats	4
Video formats: SD	4
Video formats: HD 1.5G	4
Video formats: HD 3G	5
Video formats: UHD	6
Audio formats	6
Spectrum X Codec Support	8
DV Codecs	8
MPEG Codecs	8
AVC I-Frame Codecs	8
AVC Long GOP Codecs	9
VANC and VBI Storage	11
Media Wrapper Formats and Audio Track Type Compatibility	12
Media Wrapper Formats and Supported Track Types	14
QuickTime (Reference and Self-contained)	14
QuickTime (Self-contained)	14
QuickTime (Reference)	14
MXF (Self-contained)	14
MXF OP1a (Self-contained)	15
MXF OP1a/OP1a low latency/OP1b	15
MXF OP1a/OP1a low latency	15
MXF OP1a RDD9	15
MXF OP1a EVTR	15
MXF AS-02 2009/2011	15
GXF (Play only)	15
Media Wrapper Format Workflow Limitations	17
File Imports	18

Media Formats

Spectrum Systems support the following compressed and uncompressed media formats.

Important

Check the Spectrum release notes for any issues relating to media and wrapper formats.

Video formats: SD

I/O module	Media format	Details
Spectrum X, ChannelPort, MediaPort 7000 series	DV	DV, DVCPRO, DVCPRO 50
	MPEG-2	3-24.9 Mbps LGOP, 25-50 Mbps I-frame, 30-50 Mbps IMX
ChannelPort, MediaPort 7000 series	MPEG-4	For proxy H.264

Video formats: HD 1.5G

I/O module	Media format	Details
Spectrum X, ChannelPort, MediaPort 7000 series	DV	DVCPRO HD
	XDCAM HD	18, 25, 35, 50 Mbps
	AVC-Ultra (Panasonic*)	Class 50 and Class 100, 1920x1080i (25/29.97 Hz); 1280x720p (50/59.94 Hz)
	VC-3 (For Spectrum X, play only)	120 Mbps (25/50fps); 145 Mbps (29.97/59.94 fps)
Spectrum X	XAVC-LGOP	Hi 422, Level 4, 25/50 Mbps

I/O module	Media format	Details
	AVC-LGOP	Record: AVC-Long G50/G25. Playback: AVC-Long G50/G25/G12
	RP 2027* class 50/100 (generic)	Class 100, 1920x1080i (25/29.97 Hz); 1280x720p (50/59.94 Hz)
	XAVC-I class 100 (Sony*)	Class 100, 1920x1080i (25/29.97 Hz); 1280x720p (50/59.94 Hz)
ChannelPort, MediaPort	Apple ProRes	Standard quality mode, 50/59.94 Hz, 720p, 1080i. 147 Mbps at NTSC frame rates and 122 Mbps at PAL frame rates.
ChannelPort	AVC (H.264) Long GOP	<p>AVC (H.264) Long GOP is available only when re-wrapped from PitchBlue® transport streams. (PitchBlue is a registered trademark of Vigor Systems.)</p> <p>ChannelPort supports playout of AVC at PitchBlue® operating points and AVC-Intra operating points only. Attempting to play other AVC clips may result in a failure to play.</p> <p>Support for native playout of H.264 Main Profile at Level 4; 8 bit, 4:2:0, LGOP video</p>

*Some RP 2027 files may not be supported. Contact your Harmonic representative if you wish to verify support for your material.

Video formats: HD 3G

I/O module	Media format	Details
Spectrum X	AVC I-Frame	Play and record: XAVC-Intra (Sony*), AVC-Intra (Panasonic*), AVC-I RP2027 class 100 (generic)
	XAVC-Long GOP	Play only: XAVC Hi 422, Level 4.2, up to 50 Mbps
	AVC-Long GOP	Play only: AVC-Long GOP, at 35/40/45/50 Mbps

I/O module	Media format	Details
	AVCU-Long GOP*	Play only: AVCU-Long GOP G50/G25/G12

*If using this format, contact your Harmonic representative to discuss your specific workflow.

Video formats: UHD

I/O module	Media format	Details
Spectrum X	AVC I-Frame	Play and Record <ul style="list-style-type: none"> XAVC-Intra 4:2:2 (Sony), interleaved or square division
		Play only <ul style="list-style-type: none"> AVC-Ultra 4k 4:2:2 (Panasonic), interleaved or square division

Audio formats

I/O module	Media Formats	Details
Spectrum X, ChannelPort, MediaPort 7000 series	PCM	48 kHz PCM (16, 24, 32-bit); optionally, PCM can contain AC-3 (16 bits) or Dolby® E (24 bits)

I/O module	Media Formats	Details
Spectrum X, ChannelPort	Dolby® E	<ul style="list-style-type: none"> • Support for the decoding of all encoded Dolby E (16, 20 and 24-bit) program configurations (0-23) to PCM. • Support up to four unique decodes of Dolby E per Spectrum I/O module. • Support for down mixing of Dolby E 5.1 and 7.1 (program configurations 11, 22) to stereo or mono channels. Note that 5.1+2 and 5.1+1+1 channel configurations that wish to be down mixed must be done as 5.1 with the other channels not mixed. • No support for outputting decoded down-mixed Dolby E metadata as ancillary packets. • No support for using any decoded Dolby E metadata mix levels as part of the 5.1 and 7.1 down mixing to stereo or mono channels. • For more details on Dolby E decode support, see “About Dolby E decode support” in the <i>Harmonic SystemManager User Guide</i>.
ChannelPort, MediaPort 7000 series	AAC-LC	For use with proxy H.264. Zero to 8 stereo pairs, encoded at 64, 96 or 128 Kbps.

Spectrum X Codec Support

DV Codecs

Name	Format	Bit rate (Mbps)
DV 25	SD	25
DVCPRO 25	SD	25
DVCPRO 50	SD	50
DVCPRO 100	HD	100

MPEG Codecs

Name	Format	Bit rate (Mbps)
MPEG-2 Long GOP	SD	3-24.9
	HD	18-85
MPEG-2 I-Frame	SD	25-50
	HD	50-100
IMX (also called XDCAM or EVTR)	SD	30, 40, 50
XDCAM-HD XDCAM-HD RDD9 (wrapper)	HD	18, 25, 35, 50

AVC I-Frame Codecs

Name	Class	Sampling	Bit depth
XAVC-Intra	50	4:2:0	10 bit
	100	4:2:2	10 bit
	300	4:2:2	10 bit

Name	Class	Sampling	Bit depth
AVC-Ultra	50	4:2:0	10 bit
	100	4:2:2	10 bit
	400	4:2:2	10 bit
AVC-I (RP2027)	50	4:2:0	10 bit
	100	4:2:2	10 bit

Note: For 3G records with I-Frame formats:

- In *internal storage* mode, Spectrum X supports two channels.
- In *shared storage* mode, Spectrum X supports four channels.

Note: Bit rates for 3G material are approximately double for material of the same class at HD.

Note: For UHD record, Spectrum X supports one channel of XAVC-Intra Class 300 with the MXF OP1a wrapper.

AVC Long GOP Codecs

Name	Class	Sampling	Bit depth
AVCu-Long GOP*	G50	4:2:2	10 bit
	G25	4:2:2	10 bit
	G12	4:2:0	8 bit

*If using this format, contact your Harmonic representative to discuss your specific workflow.

Note: Bit rates for 3G material are approximately double for material of the same class at HD.

Name	Sampling	Bit depth	Bit rate (Mbps) for 1080i	Bit rate (Mbps) for 720p	Bit rate (Mbps) for 1080p
XAVC-Long GOP	4:2:2	10 bit	25/35/50	50	35/50
AVC-Long GOP	4:2:2	10 bit	15/20/25/30/35/40/45 /50	15/20/25/30/35/40/45 /50	35/40/45/50
	4:2:0	8 bit	15/20/25/30/35/40/45 /50	15/20/25/30/35/40/45 /50	35/40/45/50

Note: For 3G Long GOP formats, Spectrum X supports play only.

VANC and VBI Storage

The following table shows supported VANC and VBI Storage media types.

Metadata Type	Video Media Type	Embedded Video	Side-Band
Uncompressed VBI	Standard Definition MPEG-2	Omneon user data	Omneon VBI File (QuickTime only)
			GXF VBI track
	DV, DVCPRO, DVCPRO50	Unavailable	Omneon VBI File (QuickTime only)
			GXF VBI track
			SMPTE 436M (MXF OP1a only)
			GXF VBI track
VANC	High Definition	SMPTE 328M	SMPTE 436M (MXF OP1a only)
	MPEG-2		GXF VANC track
	DVCPRO HD	SMPTE 375M	
	AVC-Ultra	Panasonic Spec	
	Others	Unavailable	


Please note the following:

- Capture and playout of SD VANC information is supported. Contact Harmonic Technical Support for additional information.
- SMPTE 328M: VANC is stored in the MPEG-2 user data.
- SMPTE 436M: HD and SD VANC is stored in MXF SMPTE 436M track.
- Omneon VBI File: VBI data is stored in an Omneon proprietary format in the clip.
- Panasonic Embedded: For AVC-Ultra the Panasonic specification describes a technique for storing VANC in the essence.
- DV Embedded: This is stored in the essence according to SMPTE 374/375/376. For SD VANC formats, only audio, timecode, and closed caption data are stored.

Media Wrapper Formats and Audio Track Type Compatibility

The following table shows supported combinations of audio types and media wrapper formats.

Wrapper Format	AIFF (Big Endian)	WAV (Little Endian)	AES3	8-bit A law
QuickTime Reference	Total of (2, 4, 6, 8, 10, 12, 14, or 16) audio channels recorded with (1, 2, 4, or 8) channels per file or per track with sample size (16 or 24) bits.		No	No
QuickTime Self-Contained				
MXF OP1a (Standard)				
MXF OP1b (External)				
MXF OP1a (eVTR)	N/A		Total 8 audio channels recorded with 8 channels per file with 24-bit samples stored in 32 bits each.	N/A
MXF AS-02 (2009, 2011)	Total of (2, 4, 6, 8, 10, 12, 14, or 16) audio channels recorded with (1, 2, 4, or 8) channels per file with sample size (16 or 24) bits.		No	No
MXF OP1a (Standard and Low Latency)				Yes

Wrapper Format	AIFF (Big Endian)	WAV (Little Endian)	AES3	8-bit A law
MXF OP1a (SMPTE RDD9 and Internal, early Sony style XDCAM-HD RDD9)	No	Total of (2, 4, 6, or 8) audio channels recorded with 1 channel per file with sample size (16 or 24) bits. <div style="border: 1px solid #ccc; background-color: #ffffcc; padding: 10px; margin-top: 10px;">  Note 16 audio channels are supported but such configurations may not work with all software or devices that expect compliant material. </div>	No	No
MXF ARD_ZDF_HDF (01a, 01b, 02a, 02b, 03a, 03b)	No	8 or 16 mono tracks	No	No
GXF (Play only)*	No	Total of (1, 2, 4, 8, 10, 12, 14, or 16) audio channels with 1 channel per file with sample size (16 or 24) bits.	No	No

Please note the following about support for GXF:

- GXF is a read-only format. It is a serialization of Grass Valley's native asset. If it is necessary to make any modifications to a GXF clip for use on Spectrum systems, Harmonic suggests rewrapping the clip into either an MXF or QuickTime format.
- GXF-wrapped clips must have a ".gxf" extension.
- Offspeed play and shuttle/jog of GXF clips is not supported.
- "Complex GXF" and "Compound GXF" clip types are not supported. Only "Simple GXF" clip types are supported.

Media Wrapper Formats and Supported Track Types

The following are supported combinations of media wrapper formats and track types.

Note

3G material is supported only with MXF OP1a wrapper formats.

Note

UHD material is supported only with the MXF OP1a wrapper format.

QuickTime (Reference and Self-contained)

- DV, DVCPRO, DVCPRO 50, DVCPRO HD
- MPEG-2: I-Frame, IMX, LGOP
- VC-3
- ProRes
- Audio

QuickTime (Self-contained)

- MPEG-4
- AVC-Ultra, AVC (H.264) Long GOP

QuickTime (Reference)

- For *play* only: AVC-Ultra, AVC (H.264) Long GOP

MXF (Self-contained)

- MPEG-4

MXF OP1a (Self-contained)

- XAVC-Intra 4:2:2
- AVC-Intra 4K 4:2:2

MXF OP1a/OP1a low latency/OP1b

- DV, DVCPRO, DVCPRO 50, DVCPRO HD
- MPEG-2: I-Frame, IMX, LGOP
- VC-3
- AVC-Ultra, AVC (H.264) Long GOP
- Audio

MXF OP1a/OP1a low latency

- XAVC-I class 100, RP 2027 class 50/100

MXF OP1a RDD9

- MPEG-2 LGOP
- Audio

MXF OP1a EVTR

- MPEG-2 IMX
- Audio

MXF AS-02 2009/2011

- DV, DVCPRO, DVCPRO 50, DVCPRO HD
- MPEG-2: I-Frame, IMX, LGOP
- Audio

GXF (Play only)

- DV, DVCPRO, DVCPRO 50, DVCPRO HD

- MPEG-2: I-Frame, IMX, LGOP
- AVC-I class 50, AVC-I class 100
- Audio

Media Wrapper Format Workflow Limitations

Media Wrapper Format	Play Behind Record	Play Behind FTP	FTP Behind Record	Active Transfer Behind Record
QuickTime (referenced and self contained)	supported	not supported	not supported	supported
Op1a standard	supported	supported**	not supported	supported
Op1a low latency (standard, eVTR, RDD9)	supported*	supported**	supported	supported
Op1b	supported	not supported	not supported	supported
AS-02	supported	not supported	not supported	supported

*Op1a low latency play behind record limitations:

- Play behind record is supported when the player recording the clip and the player playing the clip are on the same Spectrum server.
- If the player recording the clip and the player playing the clip are on different Spectrum servers sharing an EFS, play behind record is supported with the following "Op1a play behind FTP limitations."

**Op1a play behind FTP limitations:

- Play behind FTP is supported when playing at normal speed from the beginning of the clip.
- Play behind FTP is supported when playing at normal speed from an offset into the clip when the time code is continuous (including pre-charge) and it is the first or only clip in the playlist.
- When playing off speed, frames may be dropped and black frames may be played.
- When playing from an offset into the clip and the time code is not continuous, the start of play may not be frame accurate.
- When playing from an offset into the clip and it is not the first clip in the playlist, black frames may play before the clip starts to play.

File Imports

By creating a "watch folder" on your Spectrum system, you can configure Spectrum to demultiplex transport stream files from a PitchBlue® system or MPEG-2 program stream files, or re-wrap LXF files that are transferred via FTP or Samba to the specified "watch folder" on your Spectrum video server.

For demultiplexed transport stream files, the resulting AVC/H.264 files can be played out with a Spectrum I/O module licensed for AVC/H.264.

For details and configuration instructions, see "Configuring Watch Folders" in the *Harmonic SystemManager User Guide*.

About support for the LXF wrapper format

Harmonic supports the LXF wrapper format only for files that are imported into a Spectrum "watch folder," and then re-wrapped as described in the "Configuring Watch Folders" section of the SystemManager User Guide. Harmonic does not support the playout of native LXF files.